


STRIP BLACK 224LED/M 6W/M 30K IP65

Code: 06851

The Black stripLED Professional line is the best choice in terms of performance, efficiency and light quality. These strips are characterized by a uniform color and high color rendering, brilliant and sharp in every context. CRI95, R9>60.





General specifications

Plack professional
Black professional
Exterior
3M 300 LSE biadhesive
IN/OUT
Box
Albania

Physical specifications

IP	IP65

Lighting specifications

N° LEDs / m	224
Lm/m	833
W / m	6
Light type	White
ССТ	3000K
CRI	95
R9	60
Chromatic tolerance (SDCM)	3
RG	RG1
Life time	L90B10
LB value @ h	50000



Light Emission Specifications

Beam (°)	120

Electrical specifications

Power supply availability	Not included
Dimmable	Yes
Dimmer availability	Not included
Power (W)	30
Power supply voltage type	DC
Power supply type (CC / CV)	Voltage
Input Voltage MIN-MAX (V)	24
Insulation class	III
Light source type	LEDs SMD
LED packaging	2835
Feedback	5000
Energy efficiency class	D
Replaceable light source	Replaceable by skilled personnel

Dimensions and weight

Length (mm)	4988
Width (mm)	10
Height / Thickness (mm)	4
Cable IN length (mm)	100
Cable OUT length (mm)	100
Minimum bending radius (m)	5
Module length (mm)	31.25

General conditions

Warranty	2 years
Operating temperature (ambient)	-10°C (min) / 45°C (max)
Storage temperature	-20 °C (min) / 50 °C (max)