


# PERFETTO-IN 70 MAX12W 3000K CRI90 44°

Code: 262-039BNW-21

Professional downlight with a fixed optic, able to provide high luminous performance, thanks to the COB LED of the last generation. The rearward optic and the integrated snoot improve the visual comfort considerably, making it the ideal luminaire for the illumination both in residential and in hospitality, as well as in some retail applications. Perfetto-IN 70 integrates into spaces in a soft and elegant way: its very thin trim allows an almost invisible installation in the false ceiling. Optical accessories are available. Protection rating IP43. LED drivers should be ordered separately; the wattage of the fittings changes, depending on the selected driver.





#### **General specifications**

Designer	Ivela Design Team
Installation environment	Interior
Native mounting type	Rebated flush-mounted
Mounting type	Rebated flush-mounted
Ideal application locations	Residential, Hospitality, Showroom, Museum, Office, Commercial space
Packaging	Вох
Wire incandescent test	850
Made in	Italy

### **Physical specifications**

Shape	Round
Body material	Aluminum
Body finish	Matte
Body color	White
Frontal material	Aluminum
Frontal finish	Embossed
Frontal color	White
Thermal dissipation	Passive
Covering with insulating materials	No



IP back	IP20
IP	IP43
Waterstop	No
Salt mist resistance	No

#### Lighting specifications

Lumen	853
L.O.R. (%)	58
Power	12
W source	12
Light type	White
CCT	3000K
CRI	90
Life time	L80B10

# **Optical specifications**

Light beam distribution	Symmetric
Beam	44
Optics type	Symmetrical optical lens
Optical diffuser finish	Metallized
Optical diffuser material	Termoplastic
Orientability	Fixed

## **Electrical specifications**

Power supply availability	Not included
Power supply position	Remote
CV / CC converter position	Remote
Dimmable	Yes
Dimming type	ON/OFF
Power supply type	Current
Insulation class	Ш

# **Dimensions and weight**

Height / Thickness (mm)	83
Diameter (mm)	70
Recessed hole width (mm)	64
Recess depth (mm)	83

#### **General conditions**

Warranty	5 years